

This information is given as an indication. In the continual goal to improve our products, we reserve the right to make any modifications judged necessary

2 W

DC-12.4GHz


SMA

COAXIAL ATTENUATOR

Issue
28.jul.93

Page
1 / 1

DRAWING



General tolerances: +/- 0.5 mm

R F CHARACTERISTICS

FREQUENCY RANGE : DC - 12.4GHz
IMPEDANCE : 50 Ohms
ATTENUATION - NOMINAL : 11 dB

FREQUENCY	DC- 4 GHz	4 -12.4GHz
V.S.W.R	<= 1.15	<= 1.25
DEVIATION (dB)	+0.5 / -0.5	+0.5 / -0.5

TEMPERATURE SENSITIVITY : 4×10^{-4} dB
dB * °C

PEAK POWER at 25°C (1µs,1%) : 100 W


AVERAGE POWER at 25°C : 2 W

MECHANICAL CHARACTERISTICS

CONNECTORS : SMA male/female per MIL-C 39012
WEIGHT : < 5 g

ENVIRONMENTAL CHARACTERISTICS

OPERATING TEMPERATURE RANGE (°C) : -55 , +125
STORAGE TEMPERATURE RANGE (°C) : -55 , +125



QUALITY R4
Dpt app. e

CREATION

PEN : CAT

EP : -----

Nom : DP

Date: 02.mar.89

28.jul.93

New format

ISSUE

REVISIONS

VE

NAME

RADIALl®

101. Philibert Hoffmann
- Z.I Ouest -
93116 ROSNY/BOIS Cedex-FRANCE
Phone: 33.1.49363535
Fax : 33.1.40546363
Tvx RADIA 235220F