


A



COMPONENTS	MATERIALS	PLATING (μm)
Body	PEEK	
Center contact	BERYLLIUM COPPER - BRONZE	NPGR
Outer contact		-
Insulator		
Gasket		
Others parts		
-	-	-
-	-	-

PAGE 2/3

ISSUE
17-11-22A

SERIES IMP SR

PART NUMBER **R107838000**

PACKAGING

Standard	Unit	Other
1	Contact us	Contact us

ELECTRICAL CHARACTERISTICS

Impedance	NA	Ω
Frequency	NA	GHz
VSWR	NA + 0,000	x F(GHz) Maxi
Insertion loss	NA	√F(GHz) dB Maxi
RF leakage	- (NA	- F(GHz)) dB Maxi
Voltage rating	225	Veff Maxi
Dielectric withstanding voltage	500	Veff mini
Insulation resistance	1000	MΩ mini

MECHANICAL CHARACTERISTICS

Center contact retention		
Axial force – Mating End	0.5	N mini
Axial force – Opposite end	NA	N mini
Torque	NA	N.cm mini

Recommended torque		
Mating	NA	N.cm
Panel nut	NA	N.cm

Mating life	50	Cycles mini
Nominal Weight (Add +15% for max weight)	0,737	g

ENVIRONMENTAL

Operating temperature	-55/+125	°C
Hermetic seal	NA	Atm.cm3/s
Panel leakage	NA	

SPECIFICATION

OTHER CHARACTERISTICS

Assembly instruction:

Others:

CUSTOMER'S APPROVAL	
Department or Company's stamp	
Name :	
Date :	
Copy to send back to RADIAL S.A BEFORE :	

PAGE 3/3

ISSUE
17-11-22A

SERIES IMP SR

PART NUMBER **R107838000**

