


PROPRIETARY INFORMATION
NOT TO BE RELEASED
WITHOUT WRITTEN PERMISSION
FROM AN AUTHORIZED
REPRESENTATIVE OF
APPLIED ENGINEERING PRODUCTS

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	01/08/08	A.D.M.




NOTES:

MATERIALS:

1. BODY & CONTACT= BRASS PER ASTM B16, ALLOY C36000, TEMPER H02.
2. INSULATOR = VIRGIN WHITE TEFLON PER ASTM D1710, GRADE 1, TYPE I, CLASS "B".

FINISHES:

1. BODY = GOLD PLATE PER MIL-G-45204, TYPE II, CLASS 0, GRADE C, OVER .00010 TO .00020 COPPER STRIKE PER MIL-C-14550.
2. CONTACT = GOLD PLATE PER MIL-G-45204, TYPE II, CLASS 1, GRADE C, OVER .00010 TO .00020 STRESS FREE SULFAMATE NICKEL PER QQ-N-290.

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ON		DWN: A.D.M.	DATE 01/08/08	 APPLIED ENGINEERING PRODUCTS 104 John W. Murphy Dr. New Haven, CT 06513
		CHKD: D.N.	DATE 01/08/08	
DECIMAL	ANGLE	APVD: J.M.	DATE 01/08/08	SMC STRAIGHT MALE JACK (2) HOLE FLANGE MOUNT SOLDER POT RECEPTACLE
REFERENCE:		MATERIALS AND FINISHES: SEE NOTES		
ORIGINATOR: A.D.M. DATE: 01/08/08		SIZE A	FSCM NO. 19505	DWG. NO. 1486-1511-000 REV A
		SCALE 6:1	THIRD ANGLE PROJECTION	SHEET 1 OF 1

1486-1511-000