




1. CONTACT = GOLD PLATE PER ASTM B488-11, TYPE II, 50µin MIN, GRADE C, OVER 100 TO 200µin STRESS FREE SULFAMATE NICKEL PER AMS-QQ-N-290.
2. BODIES & CAP = GOLD PLATE PER ASTM B488-11, TYPE II, 30µin MIN, GRADE C OVER 100 TO 200µin COPPER STRIKE PER AMS 2418.

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ON		DWN:	DATE	Property of Radiall This document cannot be reproduced or communicated to a third party without prior written permission of RADIALL.				
		C.E.	03/28/18					
DECIMAL	ANGLE	CHKD:	DATE	 a RADIALL company				
		D.N.	03/28/18					
		APVD:	DATE					
		J.M.	03/28/18					
REFERENCE:		MATERIALS & FINISHES:		SMC RIGHT ANGLE MALE TOP LAUNCH JACK WITH REMOVABLE REAR CONTACT				
ORIGINATED: C.E. DATE: 03/28/18		SEE NOTES		SIZE	FSCM NO.	DWG NO.	REV	
				A	19505	1092-1511-002	A	
				SCALE 5:1	THIRD ANGLE PROJECTION 		SHEET 1 OF 1	

1092-1511-002