

NOTES:



MATERIALS:

1. FRONT INSULATOR = VIRGIN WHITE TEFLON PER ASTM D1710, GRADE 1, TYPE I, CLASS "B".
2. INSULATOR = TORLON (POLYAMIDE-IMIDE) TYPE 4203 PER ASTM D5204.
3. ALL METAL PARTS = BERYLLIUM COPPER PER ASTM B196, ALLOY C17300, TEMPER TD04.

FINISHES:

1. ALL METAL PARTS = GOLD PLATE PER MIL-G-45204, TYPE II, CLASS 1, GRADE C, OVER .00010 TO .00020 STRESS FREE SULFAMATE NICKEL PER QQ-N-290.

Property of Radiall Incorporated
This document cannot be reproduced or
communicated to a third party without prior
written permission of RADIALL Incorporated.

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ON		DWN: D.N.	DATE 03/18/10	 APPLIED ENGINEERING PRODUCTS 104 John W. Murphy Dr. New Haven, CT 06513 a RADIALL company
DECIMAL	ANGLE	CHKD: A.D.M.	DATE 03/18/10	
		APVD: J.M.	DATE 03/18/10	SMP STRAIGHT MALE SMOOTH BORE BULKHEAD MOUNT DIRECT SOLDER TYPE FOR .086 S/R & SIMILAR CABLES
REFERENCE: 1008187 ORIGINATED: D.N. DATE: 03/18/10		MATERIALS & FINISHES: SEE NOTES		
		SIZE A	FSCM NO. 19505	DWG NO. 7502-1582-110
		SCALE 8:1	THIRD ANGLE PROJECTION 	
		REV A		
		SHEET 1 OF 1		

7502-1582-110