

## ENGAGING FACE

MATERIALS AND FINISHES:

- OUTER BODY AND INNER CONTACTS: BERYLLIUM COPPER ALLOY PER ASTM B 196
- FERRULE : BRASS PER ASTM B 455
- INSULATOR : TEFLON PFA PER ASTM D 3307-00 OR ASTM D 1710
- SPACER : PEI ULTEM PER ASTM D 5205

ALL METALLIC PARTS : GOLD PLATE PER SAE AMS 2422 , 50 MICROINCHES MINIMUM  
OVER A NICKEL PLATE PER SAE AMS-QQ-N-290, CLASS 2  
100 MICROINCHES MINIMUM


EXTRACTION TOOL: M 81969/28-03 or M81969/14-06 ( RADIALL 282 549 001)

WIRING INSTRUCTIONS: RP58866

NOTE:

- NOTE:**  
- MATING INTERFACE AND OUTER DIMENSIONS COMPLIANT TO EN3155-075 STANDARD.

**DIMENSIONS : mm (inch are given for information only)**



**Estimated weight : 4,30 g**

<b>CREATION</b>  <b>PEN:</b> 10032-21003797  <b>NOM:</b> GARCIA L.  <b>DATE:</b> Dec. 7, 2021  <b>APPR.:</b> PERRIN H.				
	<b>Issue</b>	<b>Revisions</b>	<b>Name</b>	<b>Approved</b>

670075025EN

**RADIAL PROPRIETARY INFORMATION**

This document contains proprietary information and such information shall not be disclosed to any third party for any purpose whatsoever or used for manufacturing purposes without prior written agreement from RADIAL. This information is given as an indication. In the continual goal to improve our products, we reserve the right to make any modifications judged necessary.