

**Cable stripped length:**


**MATERIAL AND FINISH:** COPPER ALLOY PER UNS C18700 CHEMICAL COMPOSITION AND GOLD OVER NICKEL.

CRIMPING TOOL : M22520/23-01  
DIE SET : M22520/23-02  
LOCATOR: RADIALL P/N: 282 588  
REMOVABLE TOOL : RADIALL P/N: 282 549 001

Note:

In order to ensure the SAE AS39029 tensile strength requirements for any wire plating, RADIALL recommend to use MS3348-8-10 bushing when crimped to AWG 10 cable.

**DIMENSIONS : mm (inch are given for information only)**



Estimated weight : 4 g

<b>CREATION</b>  <b>PEN: M060400099A</b>  <b>NOM: PAILOT N.</b>  <b>DATE: Oct 17, 2006</b>  <b>APPR.: PESSARD M.</b>				
	Jul. 12, 18	Dimensions corrected, in accordance with standard FN3155-076	LOPEZ C.	WEIHS H.
	Feb. 23, 18	Material note updated	MOUTAULT W.	LEGLOAHEC Y
	Oct 20, 14	Note added	YON P.	VIEIRA D.
	Jan. 07, 13	Dimensions corrected, in accordance with standard FN3155-076	VIEIRA D.	LEGLOAHEC Y
	Issue	Revisions	Name	Approved