


MATERIALS:

- BACKSHELL & CLAMP: High grade thermoplastic,
- METALLIC INSERTS: Copper nickel zinc alloy,
- CAPTIVE SCREWS: Stainless steel,
- BUSHING: Fluorosilicone elastomer.

NOTES:

- Strain relief delivered with the clamp, captive screws, and the bushing are uninstalled,
- 4-40 captive screws locking torque: 0,50 ±0,10 N.m,
- Optical cable diameter range compatibility: Ø2,62mm [0,103in] - Ø3,18mm [0,126in],
- Remove the straight fiber optic backshell for cable or insert maintenance,
- Refer to MIBS1700020 for mounting instruction.

DIMENSIONS : mm (inch are given for information only)



Estimated weight : 12 g

<p>CREATION</p> <p>PEN: 20164893</p> <p>NOM: POLINE E.</p> <p>DATE: Mar. 22, 2016</p> <p>APPR.: POLINE E.</p>				
	Apr. 09, 2019	TDS updated. Correction on dimensions on lateral view: from [0,909 max] to [0,910 max] & from [1,169] to [1,170].	Lopez C.	Weihs H.
	Dec. 08, 2017	Updated title	Legendre T.	Surault S.
	Oct. 18, 2017	Updated dimensions	Weihs H.	Moutault W.
	Apr. 14, 2017	Was manufactured in Aluminium alloy	Pailot N.	Legloahec Y.
	Issue	Revisions	Name	Approved

617921044EN

RADIALL PROPRIETARY INFORMATION

This information is given as an indication. In the continual goal to improve our products, we reserve the right to make any modifications judged necessary. This information shall not be disclosed to any third party for any purpose whatsoever or used for manufacturing purposes without prior written agreement from RADIALL.