

**MATERIAL:**

- OUTER CONTACT : BERYLLIUM COPPER PER ASTM B 196
- CENTER CONTACT : BERYLLIUM COPPER PER ASTM B 196
- FERRULE : BRASS PER ASTM B 16 OR ASTM B 453 OR EN 12164
- DIELECTRIC : PTFE PER ASTM-D-1710 OR EQUIVALENT
- SEALING BOOT : THERMOPLASTIC PER ASTM D 5205 AND FLUOROSILICONE PER SAE AMS-R-25988

FINISHES:

- FERRULE, OUTER AND CENTER CONTACTS : PLATING .00005 INCH OF GOLD PER SAE AMS-2422 OVER NICKEL PER AMS 2403

**TOOLING:**


- CENTER CONTACT : CRIMPING TOOL M22520/2-01 (RADIAL 282281)  
SELECTOR ON 5  
POSITIONNER 282587 (DANIELS K1025-S)
- FERRULE : CRIMPING TOOL M22520/5-01 (RADIAL 282293)  
DIE M22520/5-05 (RADIAL 282246)  
HEX B 4,50 (.177) ON FLATS

**EXTRACTION TOOL:**

- M81969/28-03 RADIAL 282549001

**WIRING INSTRUCTIONS: SEE MICT0100052**

**DIMENSIONS : mm (inch are given for information only)**



Estimated weight : 4,40 g

<b>CREATION</b>  <b>PEN:</b> 21002882  <b>NOM:</b> BRANJONNEAU V.  <b>DATE:</b> Jan. 24, 2022  <b>APPR.:</b> LEGENDRE T.				
	<b>Issue</b>	<b>Revisions</b>	<b>Name</b>	<b>Approved</b>