

MATERIAL :

OUTER CONTACT, CLAMP NUT, WASHER BUSHING AND BRAID CLAMP : BRASS PER ASTM B 16/B 16M OR EQUIVALENT
CENTER CONTACT : BERYLIUM COPPER PER ASTM-B-196
INSULATOR : PTFE PER ASTM-B-1710 OR EQUIVALENT
RETAINING BLOC : ALUMINIUM ALLOY PER SAE AMS-QQ-A-250
SPRING, FLAT WASHERS, C'CLIP AND SCREWS : CORROSION RESISTANT MATERIAL
O'RING AND GASKET : FLUOROSILICONE ELASTOMER PER SAE AMS-R-25988


FINISH :

ALL METALIC PARTS : .00005 INCH OF GOLD PER SAE AMS-2422 OVER NICKEL PER SAE AMS-QQ-N-290 (CLASS 2)
RETAINING BLOC : BLACK ANODIZED PER MIL-A-8625

WIRING INSTRUCTION :

SEE WIRING INSTRUCTION : MI CT 01 00031

DIMENSIONS : mm (inch are given for information only)



Estimated weight : 42 g

CREATION PEN: 1009529 NOM: FORET H. DATE: Oct.15, 1985 APPR.: /				
	May 05, 14	Remove NGC875BAR-1 cable	Ramos	Dupuis
	Sep. 07, 11	Add NGC875BAR-1 cable (validated)	Moutault	Dupuis
	July.06, 11	Wiring instruction separated and TDS redraw	Moutault	Brochet
	May. 15, 07	Wiring instruction added page 2	/	/
	Nov. 18, 05	Updated material and finish	Valgresy	Lahoreau
	Oct. 01, 02	Redraw	Valgresy	Dupuis
	Issue	Revisions	Name	Approved

620103EN

RADIALL PROPRIETARY INFORMATION