



All dimensions are in mm.

DESCRIPTION

REP	COMPONENT	MATERIALS	PLATING
1	TIGHTENING CONE	PA6.6	NA
2	COUPLING NUT	ALUMINIUM (mat finish)	NONE
3	PLUG PROTECTION CAP	PBT GF	NA
4	CLAMP NUT ELASTIC SHELL	PA6.6	NA
5	NUT TAIL OF PIG	PA6.6 GF	NA
6	SEALING CAP GASKET	SILICONE	NA
7	O-RING BODY GASKET	SILICONE	NA
8	CLAMP SPLIT GASKET	NITRILE (NBR)	NA
9	UNLOCKING CLIP	PA6	NA
10	SHORT BODY	ZAMAK 5	NICKEL OVER COPPER

PAGE 2/2

ISSUE **19-03-15B**

SERIES **R2CT**

PART NUMBER **R2CT125000**

GENERAL CHARACTERISTICS

Mechanical Mating endurance (cycles) Axial Tensile load (N min) Vibration Bumps Recom. coupling torque (N.cm) Weight (g)	IEC 61300-2-2 IEC 61300-2-4 IEC 60512-6-4 IEC 60068-2-29	200 200 Compliant Compliant 350 134
Environmental Protection class (mated condition) Operating temperature (°C) Storage temperature (°C) Salt Mist RoHS	IEC 60529 IEC 61300-2-22 IEC 61300-2-22 IEC 60068-2-11 -	IP65 (*) -40 / +85 -40 / +85 96h Compliant
Others: Cable Packaging		Cable Diameter from 6.5 to 7.1 mm (field cable only) Unitary in plastic bag with assembly note.

(*) Mated condition