



CABLES : -

CHARACTERISTICS

NOMINAL IMPEDANCE	50 Ω
FREQUENCY RANGE	0-2 GHz
TEMPERATURE RATING	-55/+155 °C
VSWR	NA + 0 x F(GHz)Maxi
RF INSERTION LOSS	- √F(GHz) dB Maxi
VOLTAGE RATING	- Vrms Max
DIELECTRIC WITHSTANDING VOLTAGE	8000 Vrms min
INSULATION RESISTANCE	- MΩ min
HERMETIC SEAL	- cc/s NA Atm.cm3/s
LEAKAGE (pressurized only)	- psi 0.35 MPa
WEIGHT	0.5357 Oz 15 g

STANDARDISATION

CABLE RETENTION	0	lb min N
CENTER CONTACT RETENTION		
Axial force - mating end	6.06	lb min N
Axial force - opposite end	6.06	lb min N
Torque (Min)	0	Inch.oz cm.N
RECOMMENDED TORQUES		
Mating	0	Inch.lb cm.N
Panel nut	28.32	Inch.lb cm.N
Clamp nut	0	Inch.lb cm.N

CONSTRUCTION

CONNECTOR PARTS	MATERIALS	FINISH
BODY	BRASS	NICKEL
OUTER CONTACT	BRASS	NICKEL
CENTER CONTACT	BERYLLIUM COPPER	SILVER
INSULATOR	PTFE	-
O-RING	SILICONE RUBBER	-
-	-	-
-	-	-
-	-	-
-	-	-

ISSUE	REVISION No	DESCRIPTION	BY	DATE
.
.
.
.

Initiated on 02/02/94

The information given here is subject to change without notice. Design changes may be in order to improve the product.



Approval by TRIQUES E.

GAUTIER