

Stripping tool

R299550000



Precision stripping tool for removing the sheath from signal, telephone, audiovisual, instrumentation and data transmission copper and fiber optic cables. Up to Ø 11 mm/0.43 inch.

- **Precise:** Fine adjustability and repeatability assured by 9-position adjustment wheel.
- **Easy to use:** Simply squeezing Oden together opens the stripping cavity – insert cable, rotate once, remove from cable and pull off the scrap insulation sheath.
- **Safe:** Smooth, rounded, pocketable and lightweight design. No open blade. Replacement blades encased within a plastic cassette.
- **Flexible:** Strips the sheath from most multi-core and fiber optic cables up to 11 mm/0.43 inch in diameter.
- **Economic:** Replacement blade cassettes available.

TECHNICAL DATA

Length: 90.5 mm/3.56"

Width: 39.8 mm/1.57"

Height: 18.5 mm/0.73"

Weight: 28 gr/0.06 lb

Wire size: 2.5-11 Ø mm / Ø 0.10"-0.43"

Stripping dimensions mm/mm²: adjustable/up to 1 mm (insulation thickness)

Stripping dimensions inch/AWG: adjustable/up to 0.04" (insulation thickness)

Cable: Data / Signal

Description: Adjustable precision stripping tool for signal, telephone, audiovisual, instrumentation and data transmission copper and fiber optic cables.

Life span, cycles: 50,000